

**CAUTION: Risk of product damage.**

- It is advisable always to run in some cold water before turning on the hot tap
- Do not use abrasive cleaners.
- Wipe your bath with a soft cloth after each use to prevent a build-up of soap and residue.
- Avoid cleaning products that contain acetone, ethyl alcohol, amyl or ethyl acetate, sodium hypochlorite, toluene, or phenol. These products can damage the finish
- Extreme heat such as that generated by cigarettes or portable heaters can damage Acrylic surfaces. Do not use such items near your bath.
- In the event of slight scratches in the bath surface, a mild abrasive, similar to metal polish, can be used to polish these out.

**FOR TECHNICAL ADVICE/ SPARE PARTS  
PLEASE CONTACT OUR CUSTOMER  
SERVICES DEPARTMENT**

Tel. 519-690-0009 Fax. 519-690-0008

**TO THE INSTALLER**

Please leave the instruction leaflet for the customer

Clearwater Collection Ltd

**clearwater**   
COLLECTION

**The Saturn Bath  
Installation Instructions**



**Please read carefully prior to commencing any work.**

Any installation should only be carried out by a qualified tradesman with knowledge of the Statutory Regulations and plumbing requirements for your area.

**HANDLING**

Please note that this product has been through our rigid quality control procedures which include a thorough visual inspection under bright lights water testing etc. Please unwrap the bath and check it carefully to ensure it has not been damaged in handling or transport which is beyond our control.

Do not remove the old fixture before you unpack and inspect the new unit. Upon receipt, check for shortages. Report any shortages immediately. Store the bath and wall surrounds in a safe place until you begin installation to avoid damage.

**Claims regarding cracks and/or face damage must be reported within 24 hours of receipt of the product. No such claims will be recognised after installation as this is classed as acceptance of the product.**

The bath should not be exposed to direct flame or abnormal heat. Once installed it is good practice to cover the entire bath with a soft protective cloth until other trades have completed their work.

## The Bath Instructions

This bath is suitable for plastic wastes or exposed wastes. These are available to purchase separately.

1. The bath comes with Tap holes as standard but can be ordered without at time of order.
2. The floor which the bath sits on must be level.
3. There is access at the back of the bath to attach the pipework for your taps.
4. The bath also slopes at the base to allow for the external waste pipe where necessary. (See fig 1.)

Fig 1



5. There is access under the bath for the connection of the outlet pipe to the trap.
6. The bath can be tipped up slightly to allow connection to the drain piping running into the floor void, or a length of flexible pipe can be used. (See fig. 2)

Fig 2



## Connecting the waste to the drain pipe

There are two ways in which you can connect the drain pipe to the waste.

Method 1) If you have a waste that comes up through the floor, you can connect to it with a flexible drain pipe which enables you to tilt the bath up and move the bath into the required position. To avoid water retention in the trap the flexible pipe should have a continuous downward flow

Method 2) If under-floor access is impossible, the external waste pipe can be attached to the bath waste via a shallow seal P-Trap which can be purchased separately.

### Very important

#### Check for leaks before securing to floor

Once the waste connection has been made, with the plug in, run a little water into the bath and check for leaks. Take the plug out and let water drain. Check again for leaks. Then fill the bath past the over flow, empty and check for leaks again.

#### Securing your bath to the floor

When the bath is in position and the installation is complete, It is recommended that you apply clear silicone sealant around the bottom of the bath to secure it to the floor (Circles shown in Fig 2). Should maintenance access be needed the silicone can be released by cutting round it with a sharp knife.