

CAUTION: Risk of product damage.

- It is advisable always to run in some cold water before turning on the hot tap
- Do not use abrasive cleaners.
- Wipe your bath with a soft cloth after each use to prevent a build-up of soap and residue.
- Avoid cleaning products that contain acetone, ethyl alcohol, amyl or ethyl acetate, sodium hypochlorite, toluene, or phenol. These products can damage the finish
- Extreme heat such as that generated by cigarettes or portable heaters can damage Acrylic surfaces. Do not use such items near your bath.
- In the event of slight scratches in the bath surface, a mild abrasive, similar to metal polish, can be used to polish these out.

**FOR TECHNICAL ADVICE/ SPARE PARTS
PLEASE CONTACT OUR CUSTOMER
SERVICES DEPARTMENT**
Tel. 519-690-0009 Fax. 519-690-0008

TO THE INSTALLER
Please leave the instruction leaflet for the
customer

Clearwater Collection Ltd

clearwater
COLLECTION

**The Apollo/Boat/Deco/Style/ and Trend Bath
Installation Instructions**



Please read carefully prior to commencing any work.

Any installation should only be carried out by a qualified tradesman with knowledge of the Statutory Regulations and plumbing requirements for your area.

HANDLING

Please note that this product has been through our rigid quality control procedures which include a thorough visual inspection under bright lights water testing etc. Please unwrap the bath and check it carefully to ensure it has not been damaged in handling or transport which is beyond our control.

Do not remove the old fixture before you unpack and inspect the new unit. Upon receipt, check for shortages. Report any shortages immediately. Store the bath and wall surrounds in a safe place until you begin installation to avoid damage.

Claims regarding cracks and/or face damage must be reported within 24 hours of receipt of the product. No such claims will be recognised after installation as this is classed as acceptance of the product.

The bath should not be exposed to direct flame or abnormal heat. Once installed it is good practice to cover the entire bath with a soft protective cloth until other trades have completed their work.

The Bath Instructions

This bath is suitable for plastic wastes or exposed wastes. These are available to purchase separately.

1. The bath is designed for floor or wall mounted taps.
2. The floor which the bath sits on must be level.
3. There is access under the bath for the connection of the outlet pipe to the trap. (See Fig 1.)

Fig 1



4. This access point on the base can be enlarged if required, but should not extend beyond the base up the sides walls.
5. The bath can be tipped up slightly to allow connection to the drain piping running into the floor void, or a length of flexible pipe can be used. (See fig. 2)

Fig 2



Connecting the waste to the drain pipe

There are two ways in which you can connect the drain pipe to the waste.

- Method 1) If you have a waste that comes up through the floor, you can connect to it with a flexible drain pipe which enables you to tilt the bath up and move the bath into the required position. (see fig 3) To avoid water retention in the trap the flexible pipe should have a continuous downward flow

Fig 3



- Method 2) If under-floor access is impossible, an additional hole of approx 45mm diameter can be drilled through the outer skin of the bath to allow the trap to be connected to a rigid pipe(see fig 4 and 5)

Fig 4



Fig 5



Check for leaks before securing to floor

Once the waste connection has been made, with the plug in, run a little water into the bath and check for leaks. Take the plug out and let water drain. Check again for leaks. Then fill the bath past the over flow, empty and check for leaks again.

Securing your bath to the floor

When the bath is in position and the installation is complete, It is recommended that you apply a bead of clear silicone sealant around the bottom of the bath to secure it to the floor. Should maintenance access be needed the silicone can be released by cutting round it with a sharp knife.